

GALAXY2R

TWO RAM BALERS

- Scrap Dealers
- MRF's
- Recycling Centers
- Distribution Centers
- Large Paper & Plastic Processors

Factory Start-Ups

NEXGEN provides on-site start-up and comprehensive training for your personnel on operating the baler.



NEXGEN
BALING SYSTEMS

- ▼ Advanced Structural Engineering & Construction
- ▼ Efficient, High Performance Power Packs
- ▼ More than 50 Models to Choose From
- ▼ Latest Electronics Technology
- ▼ Computerized Diagnostics
- ▼ Multi-Material Processing
- ▼ CAD Designed & Documented

GALAXY^{2R}™

TWO RAM BALERS

Features and Benefits



1. **NexDoor™** – Optional multi-purpose door serves as a bale separator, bale release, bale clamp and allows for variable bale dimensions.



2. **High-efficiency Power Unit** – Power units available from 30 HP up to 2x100 HP; TEFC motors; flooded suction pumping system with high-flow hydraulic manifold; 10 micron filtration system; pressure and current transducers; separate cooling and tier circuit; and air-to-oil cooler.



3. **Adjustable Shear Beam** – The body shear blades are adjustable from the exterior of the machine.

Heavy-duty Construction – Honeycomb structure.



4. **Shear Blades** – Ram shear blade is replaceable and reversible. Body shear blade is serrated, adjustable and replaceable.

Replaceable Liners – Replaceable tongue & groove liners provide superior wear resistance.



5. **Maestro™ Color Touch-Screen Operator Interface** and Allen Bradley Micrologix 1500 PLC programmable controller features automatic and manual controls, diagnostics and bale set-up functions.



6. **Upper & Lower Infrared Actuators** – Upper infrareds are located on the access door and are adjustable the entire height of the feed hopper.



7. **Laser Positioning** – Main ram, ejector ram, and **NexDoor™** are controlled by a laser positioning device. Tie positioning is determined by the laser and eliminates the need for a sprocketed counter wheel.



8. **Stamper** – Optional stamper automatically clears shear jams.

Full Penetration – Is standard on every model to fully compress material with every stroke produces denser bales.

Ram Hold Downs – Adjustable from the outside of the machine.

Factory Start-Ups

NEXGEN provides on-site start-up and comprehensive training for your personnel on operating the baler.

Narrow Models:

Charge Box Openings
Width: 43"
Lengths: 57", 70", 84", 102"

Wide Models:

Charge Box Openings
Width: 60"
Lengths: 70", 84", 102"

Authorized Distributor:

1-800-464-3095



Pictures in this literature are illustrative only. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Certified in compliance with ANSI Regulation Z245.5 and all OSHA standards. Products must be used with safe practices and in accordance with said regulations and standards.