



The new RamJet TC-300 TANK<sup>®</sup> is the third in the Trash Commander<sup>®</sup> Series of short, yet powerful stationary compactors. With crossed-cylinder technology, our latest compactor is the most exciting new development in the waste compaction industry. The \*3 cubic yard capacity compaction chamber is incorporated into a body that is only 9'-4 1/2" long! This allows for greater throughput capacity in applications where space is limited such as retail outlets, department stores, malls, large restaurants, grocery stores and shopping centers.

The large 67 1/2"L x 58"W clear-top opening allows for large bulky items and greater throughput capacity. The TC-300 TANK is ideal for dock feed applications. With a 4-sided, rear feed hopper, there is no need for special walk-on tops or guard rails.

\*2.27 cy. WASTEC Rating and 3.0 cy. Mfg Rating

The Trash Commander

**TANK<sup>®</sup>**

*The Shortest 3 Cubic Yard Compactor in the Industry!*



The TC-300 TANK (foreground) compared to a standard 3 cy. compactor showing the difference in overall length – yet the clear-top opening of the TANK is the same as the larger RJ-325. The picture also illustrates that if the TANK is fitted with a 4-sided, rear feed hopper, there is no need for tread plates or guard rails.

Rental & Leasing Programs Available

# TC-300 3cy. TANK *The shortest 3yd compactor in the industry!*

Designed to meet applications where space is limited, but superior strength, dependability and compaction performance are a must!

## Specifications

Model: TC-300T-	HD	HDHF
Charge Box Capacity (Mfrs. Rating) . . . . .	3.0 cy	3.0 cy
(WASTEC Standards) . . . . .	2.27 cy	2.27 cy
Clear Top Opening Width . . . . .	58"	58"
Clear Top Opening Length . . . . .	67 1/2"	67 1/2"

## Performance

Cycle Time . . . . .	77 sec.	59 sec
Total Normal Force . . . . .	54,500 Lbf.	62,700 Lbf
Normal Ram Face Pressure . . . . .	34.9 psi	40.2 psi
Ram Penetration . . . . .	13.5"	13.5"

## Hydraulics/Electrics

Remote Power Unit		
Motor . . . . .	10 hp	15 hp
3/60/230-460		
Control Voltage . . . . .	120 VAC	120 VAC
UL Label Panel Box; All Circuits Fused;		
Standard Controls: Keylock, Stop, Reverse		
Pump . . . . .	10 gpm	13 gpm
Normal, psi . . . . .	2,000 psi	2,300 psi
Cylinder Stroke (2), Inches . . . . .	55.25"	55.25"
Cylinder Bore (2), Inches . . . . .	4.5"	4.5"
Rod Diameter, Inches . . . . .	2.5"	2.5"

## Weight

5,800 lbs. . . . . 5,800 lbs

The TC-300 TANK features  
Marathon's Signature  
Series Warranty:  
3 years structure,  
2 years compments  
and 6 months labor.



The TANK has Marathon's patented **CYCON Life-Xtender**® Cyclic Control System for reliable, solid state circuitry that eliminates all pressure and limit switches, extends the life of cylinders and hoses and assures maximum compaction ratios and performance.



1-800-464-3095



Pictures in this literature are illustrative only. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Certified in compliance with ANSI Regulation Z245.2, all OSHA standards, and certified under WASTEC's Stationary Compactor Certification Program. Products must be used with safe practice and in accordance with said regulations and standards.

